

TECHNICAL SPECIFICATION			
Sl.No.	Item Description	Quantity	Units
1	Torque Wrench (Ratchet Type) Manual, required Torque(540-1380)Nm with Calibration Certificate for tightening of HSFG Bolts(M22&M20-Gr.10.9) Make : Griphold / Torque Master/ Power Master	10	Pc.
2	Socket for Torque Wrench for M22 & M20 HSFG Bolts as under :		
(a)	For M22-36mm	12	Pc.
(b)	For M20-34mm	6	Pc.
	Make : Taparia / Honiton/ Chicago Pneumatic		
3	Pneumatic Hose Pipe as per IS:446:2017 & IS:443:2022 for Pneumatic type Impact Wrench as under :		
(a)	1/2" dia of 90 Ft Length	8	Bundle
(b)	3/4" dia of 90 Ft Length	4	Bundle
	Make : Polyhose / Gates		
4	Torque Wrench (Manual Ratchet type) Extention Piece of 1" Square drive 8" long fitted in between Socket and Torque Wrench Make/Brand : Taparia / Honiton / Chicago Pneumatic	12	Pc.
5	Socket for Pneumatic type Impact Wrench as under :		
(a)	22mm dia HSFG Bolt-M36	10	Pc.
(b)	20mm dia HSFG Bolt-M34	4	Pc.
	Make : Taparia / Honiton / Chicago Pneumatic.		